

FELCO 5 Classic

Pruning shear - Good performance - Basic model

Made in Switzerland by FELCO





- Reliable: sturdy steel handles / blade and anvil blade made of high-quality hardened steel / clean, precise cut / all parts can be replaced
- · Efficient: easy cutting adjustment
- Ergonomic: non-slip coating

Our recommendation (1 1 : Recommended, 2 : Strongly recommended, 3 : Best fit)

Viticulture	***
Arboriculture	***
Horticulture	***
Parks and Gardens	***
Nursery	***
Small hand	***
Large hand	***
Left-handed	***



Accessories



FELCO 300
Picking and Trimming Snip
For a clean cut



FELCO 910 <u>Holster</u> Leather - With belt loop and clip



FELCO 990 Maintenance product Grease



FELCO 310
Picking and Trimming Snip
For grape harvesting



FELCO 912 Holster Leather - With belt clip



FELCO 902

Sharpening tool

Sharpening stone

FELCO 913 <u>Holster</u> In mock leather - With belt loop



FELCO 903
Sharpening tool
Sharpener



FELCO 980 Maintenance product Spray



Spare parts

Missing

	REF.	Designation	Composition	UCC bar code
Missing	5/3	Blade	1x 5/3	7 83929 40002 0
	5/91	Kit	2x 5/11	7 83929 40037 2
Missing	5/94	Kit	1x 4/9 + 1x 5/8	7 83929 40038 9
Missing	5/13	Handle without blade	1x 5/13 + 1x 5/5B + 1x 5/35	
Missing	5/15	Handle with anvil-blade	1x 5/15 + 1x 5/35	
Missing	5/35	Plastic coating for blade handle / anvil-blade handle	1x 5/35	
Missing	5/5B	Rivet for blade	1x 5/5B	
Missing	5/8	Bolt	1x 5/8	
Missing	4/9	Nut	1x 4/9	
	5/11	White spring	1x 5/11	



Maintenance







Cleaning

It is advisable to clean your tool after each use. If your tool is particularly dirty or subject to rusting after exposure to moisture, do not delay cleaning.

Oiling

After cleaning, it is advisable to oil the tool so as to protect it from corrosion. The oil will also unjam the tool.

Sharpening

It is advisable to sharpen your tool at least once a day, but if you feel that your tool is not cutting as well as usual, sharpen it right away!

Dismantling

It is advisable to dismantle your tool on a regular basis, but at the very latest when it appears to be jammed.

Replacement parts



vissina



Changing the blade

When the blade and the anvil-blade no longer cross, or when the blade is badly damaged, it is advisable to change it.

Regulate the working of the blade and anvil-blade by adjusting the tightening of the nut. The blade should rub against the anvil-blade over 2/3 of its length.



Changing the thumb catch

When the thumb catch is damaged and loosens when used, even when the screw is readjusted, change it.